LEICESTER CITY COUNCIL - HIGHWAY MANAGEMENT

Page 1 of 1

HIGHWAY INSPECTION REGISTER

Street : THURNCOURT ROAD, THURNCOURT WARD

Inspection Schedules: 30/06/2017 - 01/01/2017

From :

To :

001093 04,	Inspection Schedule Insp	
04/01/2017	Inspect. Date	
	Inspected By	
16175396, 16175397, 16175398	Works Orders	
Repairs	Notes	

Revision 1.4

		Council - Highway N	lanagement - Works C	rder			
CARRIAGEWAY WORKS							
Inspector			Order Num	nber 161753	96		
Urgency Category URGENCY CATEGORY B			FMIS Code	FMIS Code R100052N10033			
Street Name THURNCOURT ROAD		Issued Dat	te 04-Janu	uary-2017			
Area	THURNCOURTWARP		Complete		06-January-2017		
Locations in	Street	Size	Work to do				
Near Stat concrete	tion Lane junction next to bay joints	0.50 x 0.50 m2	'C/W POTHOLE 10 SAFE'	OOMM PATCH	OR MAKE		
Opposite Martins Shop next to layby 0.50 x 0.50 m2 'C/W POTHOLE 100MM SAFE'					PATCH OR MAKE		
Os 2A on	tarmac trench	1.00 x 0.50 m2	'C/W POTHOLE 10 SAFE'	OMM PATCH	OR MAKE		
tem Code	Description of Work			Unit	Quantity		
	Description of Work Percentage addition to rate 1/13).	s for Urgency Catego	ory B work. (see Append		Quantity 1.00		
B0160122	Percentage addition to rate			lix %			
B0160122 B0720115	Percentage addition to rate 1/13). Hot poured bitumen to joint	s or cracks in the car	riageway, maximum cra	lix %	1.00		
B0160122 B0720115 B0725301	Percentage addition to rate 1/13). Hot poured bitumen to joint width 10mm.	s or cracks in the car nd flexible pavement,	riageway, maximum cra 40mm depth.	lix % ack m m	0.50		
B0160122 B0720115 B0725301 B2010106	Percentage addition to rate 1/13). Hot poured bitumen to joint width 10mm. Saw cut to bituminous bour	s or cracks in the car nd flexible pavement, TMAC CARRIAGEW	riageway, maximum cra 40mm depth. /AY PATCH 100MM TH	lix % ack m m ICK M2	1.00 0.50 0.50		
B0160122 B0720115 B0725301 B2010106 B0720115	Percentage addition to rate 1/13). Hot poured bitumen to joint width 10mm. Saw cut to bituminous bour COMBINED RATE FOR BI Hot poured bitumen to joint	s or cracks in the car nd flexible pavement, TMAC CARRIAGEW s or cracks in the car	riageway, maximum cra 40mm depth. /AY PATCH 100MM TH rriageway, maximum cra	lix % ack m m ICK M2	1.00 0.50 0.50 0.25		
30160122 30720115 30725301 32010106 30720115 30725301	Percentage addition to rate 1/13). Hot poured bitumen to joint width 10mm. Saw cut to bituminous bour COMBINED RATE FOR BI Hot poured bitumen to joint width 10mm.	s or cracks in the car nd flexible pavement, TMAC CARRIAGEW s or cracks in the car nd flexible pavement,	rriageway, maximum cra 40mm depth. /AY PATCH 100MM TH rriageway, maximum cra 40mm depth.	lix % ack m m ICK M2 ack m m	1.00 0.50 0.50 0.25 0.50		
B0160122 B0720115 B0725301 B2010106 B0720115 B0725301 B2010106	Percentage addition to rate 1/13). Hot poured bitumen to joint width 10mm. Saw cut to bituminous bour COMBINED RATE FOR BI Hot poured bitumen to joint width 10mm. Saw cut to bituminous bour	s or cracks in the car nd flexible pavement, TMAC CARRIAGEW s or cracks in the car nd flexible pavement, TMAC CARRIAGEW	rriageway, maximum cra 40mm depth. /AY PATCH 100MM TH rriageway, maximum cra 40mm depth. /AY PATCH 100MM TH	lix % ack m m ICK M2 ack m m ICK M2	1.00 0.50 0.50 0.25 0.50 0.50		
B0160122 B0720115 B0725301 B2010106 B0720115 B0725301 B2010106 B0720115	Percentage addition to rate 1/13). Hot poured bitumen to joint width 10mm. Saw cut to bituminous bour COMBINED RATE FOR BI Hot poured bitumen to joint width 10mm. Saw cut to bituminous bour COMBINED RATE FOR BI Hot poured bitumen to joint	s or cracks in the car ad flexible pavement, TMAC CARRIAGEW s or cracks in the car ad flexible pavement, TMAC CARRIAGEW s or cracks in the car	rriageway, maximum cra 40mm depth. /AY PATCH 100MM TH rriageway, maximum cra 40mm depth. /AY PATCH 100MM TH rriageway, maximum cra	lix % ack m m ICK M2 ack m m ICK M2	1.00 0.50 0.50 0.25 0.50 0.50 0.25		
Item Code B0160122 B0720115 B0725301 B2010106 B0725301 B2010106 B0720115 B0725301 B0725301 B0725301 B2010106	Percentage addition to rate 1/13). Hot poured bitumen to joint width 10mm. Saw cut to bituminous bour COMBINED RATE FOR BI Hot poured bitumen to joint width 10mm. Saw cut to bituminous bour COMBINED RATE FOR BI Hot poured bitumen to joint width 10mm.	s or cracks in the car ad flexible pavement, TMAC CARRIAGEW s or cracks in the car ad flexible pavement, TMAC CARRIAGEW s or cracks in the car ad flexible pavement,	rriageway, maximum cra 40mm depth. /AY PATCH 100MM TH rriageway, maximum cra 40mm depth. /AY PATCH 100MM TH rriageway, maximum cra 40mm depth.	lix % ack m ICK M2 ack m ICK M2 ack m m	1.00 0.50 0.50 0.25 0.50 0.50 0.25 1.00		

Completed on

By

	Leicester City	/ Council - Highway N	lanagement - Works Ore	der		
CARRIAGEWAY WORKS						
Inspector Urgency Ca Street Name Area	tegory URGENCY CAT THURNCOURT THURNCOURT W/	ROAD	Order Numb FMIS Code Issued Date Complete by	R10005 04-Janu	97 2N100338 Jary-2017 Uary-2017	
Locations in	Street	Size	Work to do			
At Scrapto photo	oft lane junction see	0.50 x 0.50 m2	'C/W POTHOLE 100 SAFE'	MM PATCH	OR MAKE	
Nr 51 oppo tarmac pat	osite lamp column 7 on ch	2.00 x 0.50 m2	'C/W POTHOLE 100 SAFE'	MM PATCH (	OR MAKE	
Item Code	Description of Work			Unit	Quantity	
B0160122	Percentage addition to rates for Urgency Category B work. (see Appendix 1/13).				1.00	
B0720115	Hot poured bitumen to joints or cracks in the carriageway, maximum crack width 10mm.				0.50	
B0725301	Saw cut to bituminous bound flexible pavement, 40mm depth. m 0.50					
B2010106	COMBINED RATE FOR BITMAC CARRIAGEWAY PATCH 100MM THICK M2				0.25	
B0720115	Hot poured bitumen to joi width 10mm.	nts or cracks in the car	riageway, maximum crac	k m	2.00	
B0725301	Saw cut to bituminous bo	und flexible pavement,	40mm depth.	m	2.00	
B2010106	COMBINED RATE FOR	BITMAC CARRIAGEW	AY PATCH 100MM THIC	CK M2	1.00	
	_		Т	otal Cost	£ 83.39	

Completed on

By

Leicester City Council - Highway Management - Works Order							
CARRIAGEWAY WORKS							
Inspector			e = <sup>5</sup>	Order Number	161753	98	
Urgency Category URGENCY CATEGORY		EGORY B		FMIS Code	R10005	2N100338	
Street Name THURNCOURT RO		ROAD		Issued Date	04-January-2017		
Area	THURNCOURT W	ARD		Complete by	06-Jan	uary-2017	
Locations in	Street	Size	Work to	do			
Os 131 around gully 1.00 x 1.00 m2 'C/W POTHOLE 100MM SAFE'			PATCH	OR MAKE			
Near Sket	chley Close junction	6.00 x 1.00 m2		RAN SETT RELA sunken carriagew ext to it'		and adjust	
Item Code	Description of Work				Unit	Quantity	
B0160122	Percentage addition to rates for Urgency Category B work. (see Appendix % 1 1/13).					1.00	
B0720115	Hot poured bitumen to joints or cracks in the carriageway, maximum crack m 1.00 width 10mm.					1.00	
B0725301	Saw cut to bituminous bound flexible pavement, 40mm depth.				m	1.00	
B2010106	COMBINED RATE FOR BITMAC CARRIAGEWAY PATCH 100MM THICK				• M2	1.00	
B0210122	Take up or down and set aside for re-use. Granite sett paving.m26.0				6.00		
B1115265	Remove from store and on class C15/20 concret	relay. Granite sett pavir e bed 100mm thick, sur	ng in footwa face slopin	ay or paved areas g at 10 deg or less	5 m2	6.00	
				Total	Cost	£ 342.79	

Completed on

