LEICESTER CITY COUNCIL - HIGHWAY MANAGEMENT

Page 1 of 1

Inspection Schedules: 06/06/2012 - 06/06/2013

HIGHWAY INSPECTION REGISTER

Street: HEATHERBROOK ROAD, BEAUMONT LEYS WARD

From:

To:

Inspection Schedule Inspect. Date	Inspect. Date	Inspected By	Works Orders	Notes
000786	10/10/2012	Paul Hastings	12134204, 12134205	
000824	23/04/2013	Paul Hastings	13140543, 13140546	

Revision 1.4

		FOOTWAY WO	PRKS		
			Order Number	1213420	
Inspector	Paul Hastin	_	FMIS Code		5N100342
Urgency Cate	egory URGENC	Y CATEGORY B			
Street Name	HEATHER	RBROOK ROAD	Issued Date	10-Octo	ber-2012
Area	BEAUMON'	Γ LEYS WARD	Complete by	11-Oct	ober-2012
Locations in S	treet	Size	Work to do		
Os No 83		2.00 x 0.30 m2	'F/W POTHOLE 60MM F SAFE WITH BITMAC' See attached photogra location of the defect		
Os No 41		1.50 x 0.30 m2	'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photograp location of the defect'		
Os No 22		2.00 x 0.25 m2	'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photogra location of the defect'		
Os No 19 1		1.00 x 1.00 m2	'F/W POTHOLE 60MM F SAFE WITH BITMAC'		
			'See attached photograp location of the defect' 'Level out uneven footwa roots'		
Jnc Bennic	on Road	2.50 x 2.00 m2	location of the defect 'Level out uneven footwa	y caused	by tree
	on Road Description of Work		location of the defect' 'Level out uneven footwaroots' 'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photogra	y caused	by tree
tem Code	Description of Work		location of the defect' 'Level out uneven footwaroots' 'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photogral location of the defect'	y caused PATCH O	by tree R MAKE
tem Code 30160122	Description of Work Percentage addition 1/13).		location of the defect' 'Level out uneven footwaroots' 'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photogralocation of the defect' ry B work. (see Appendix	PATCH O	by tree R MAKE etail and Quantity 1.00 2.00
tem Code 30160122 30720115 31126115	Description of Work Percentage addition 1/13). Hot poured bitume width 10mm. Saw cut to bitumin	on to rates for Urgency Catego en to joints or cracks in the car nous footway, up to 60mm dep	location of the defect' 'Level out uneven footwaroots' 'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photogral location of the defect' Try B work. (see Appendix triageway, maximum crack th.	PATCH Of the property of the p	by tree R MAKE etail and Quantity 1.00 2.00
tem Code 30160122 30720115 31126115 32010105	Description of Work Percentage addition 1/13). Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE	on to rates for Urgency Catego en to joints or cracks in the car nous footway, up to 60mm dep E FOR BITMAC FOOTWAY PA	location of the defect' 'Level out uneven footwaroots' 'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photogral location of the defect' Try B work. (see Appendix riageway, maximum crack th. ATCH 60MM THICK	PATCH Of the property of the p	Part of the second seco
tem Code 30160122 30720115 31126115 32010105	Description of Work Percentage addition 1/13). Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE	on to rates for Urgency Catego en to joints or cracks in the car nous footway, up to 60mm dep	location of the defect' 'Level out uneven footwaroots' 'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photogral location of the defect' Try B work. (see Appendix riageway, maximum crack th. ATCH 60MM THICK	PATCH Of the property of the p	by tree R MAKE etail and Quantity 1.00 2.00 2.00 0.60 1.50
tem Code 30160122 30720115 31126115 32010105 30720115	Description of Work Percentage addition 1/13). Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE Hot poured bitume width 10mm. Saw cut to bitumin	on to rates for Urgency Categoren to joints or cracks in the care nous footway, up to 60mm depier to joints or cracks in the care nous footway, up to 60mm depier to joints or cracks in the care	location of the defect' 'Level out uneven footwaroots' 'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photogral location of the defect' Try B work. (see Appendix Triageway, maximum crack th. ATCH 60MM THICK Triageway, maximum crack th.	PATCH Of the physical	Part of the second seco
tem Code 30160122 30720115 31126115 32010105 30720115	Description of Work Percentage addition 1/13). Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE Hot poured bitume width 10mm. Saw cut to bitumin	on to rates for Urgency Categoren to joints or cracks in the car nous footway, up to 60mm dep E FOR BITMAC FOOTWAY Pa en to joints or cracks in the car	location of the defect' 'Level out uneven footwaroots' 'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photogral location of the defect' Try B work. (see Appendix Triageway, maximum crack th. ATCH 60MM THICK Triageway, maximum crack th.	Unit m M2	Example 2.00 2.00 2.00 2.00 1.50 1.50 0.45
tem Code 30160122 30720115 31126115 32010105 31126115 32010105	Description of Work Percentage addition 1/13). Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE	on to rates for Urgency Categoren to joints or cracks in the care nous footway, up to 60mm depier to joints or cracks in the care nous footway, up to 60mm depier to joints or cracks in the care	location of the defect' 'Level out uneven footwaroots' 'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photogralocation of the defect' Try B work. (see Appendix Triageway, maximum crack th. ATCH 60MM THICK Triageway, maximum crack th. ATCH 60MM THICK	PATCH Of the physical	Part of the second seco
tem Code 30160122 30720115 31126115 32010105 31126115 32010105 30720115	Description of Work Percentage addition 1/13). Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE Hot poured bitume width 10mm. Saw cut to bitumin	on to rates for Urgency Categoren to joints or cracks in the care flous footway, up to 60mm depied to joints or cracks in the care flous footway, up to 60mm depied footway, up to 60mm depied for BITMAC FOOTWAY Part to joints or cracks in the care flous footway, up to 60mm depied to joints or cracks in the care flous footway, up to 60mm depied footway.	location of the defect' 'Level out uneven footwaroots' 'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photogralocation of the defect' Try B work. (see Appendix Triageway, maximum crack Th. ATCH 60MM THICK Triageway, maximum crack Th. ATCH 60MM THICK Triageway, maximum crack Th. The foother footbase of the defect' The foother footbase of the defect' The foother footbase of the defect' The footbase of the defect' T	PATCH Of the property of the p	Example 2.00 2.00 2.00 2.00 1.50 1.50 2.00 2.00 2.00
Jnc Bennic tem Code 30160122 30720115 31126115 32010105 31126115 32010105 31126115 32010105	Description of Work Percentage addition 1/13). Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE Hot poured bitume width 10mm. Saw cut to bitumin	on to rates for Urgency Categoren to joints or cracks in the care nous footway, up to 60mm depier for BITMAC FOOTWAY Pren to joints or cracks in the care nous footway, up to 60mm depier for BITMAC FOOTWAY Pren to joints or cracks in the care	location of the defect' 'Level out uneven footwaroots' 'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photogralocation of the defect' Try B work. (see Appendix Triageway, maximum crack Th. ATCH 60MM THICK Triageway, maximum crack Th. ATCH 60MM THICK Triageway, maximum crack Th. The foother footbase of the defect' The foother footbase of the defect' The foother footbase of the defect' The footbase of the defect' T	PATCH Of the physical	Example 2.00 2.00 2.00 2.00 1.50 1.50 2.00 2.00 0.45 2.00 2.00 0.50
tem Code 30160122 30720115 31126115 32010105 31126115 30720115	Description of Work Percentage addition 1/13). Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE Hot poured bitume width 10mm. Saw cut to bitumin COMBINED RATE COMBINED RATE COMBINED RATE	on to rates for Urgency Categoren to joints or cracks in the care flous footway, up to 60mm depied to joints or cracks in the care flous footway, up to 60mm depied footway, up to 60mm depied for BITMAC FOOTWAY Part to joints or cracks in the care flous footway, up to 60mm depied to joints or cracks in the care flous footway, up to 60mm depied footway.	location of the defect' 'Level out uneven footwaroots' 'F/W POTHOLE 60MM F SAFE WITH BITMAC' 'See attached photogralocation of the defect' Try B work. (see Appendix Triageway, maximum crack Th. ATCH 60MM THICK	PATCH Of the property of the p	Example 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00

	То	tal Cost	£ 333.81
B2010105	COMBINED RATE FOR BITMAC FOOTWAY PATCH 60MM THICK	M2	5.00
B1126115	Saw cut to bituminous footway, up to 60mm depth.	m	2.50
B0720115	Hot poured bitumen to joints or cracks in the carriageway, maximum crack width 10mm.	m	2.50
B2010105	COMBINED RATE FOR BITMAC FOOTWAY PATCH 60MM THICK	M2	1.00
B1126115	Saw cut to bituminous footway, up to 60mm depth.	m	1.00

Completed on	Ву

		<u> </u>			
		FOOTWAY WO	ORKS		
Inspector	Paul Hasting	s	Order Numbe	r 121342	05
•	egory URGENCY		FMIS Code	R10005	5N100342
Street Name	HEATHER	BROOK ROAD	Issued Date	10-Octo	ober-2012
Area	BEAUMONT	LEYS WARD	Complete by	11-Oct	ober-2012
Locations in S	Street	Size	Work to do		
Os No 31 0.50 x 0.50 m2 'F/W POTHOLE 60MM PATCH OR MAKE SAFE WITH BITMAC' See attached photograph for detail and location of the defect 'C/W POTHOLE 40MM PATCH OR MAKE SAFE' 'See attached photograph for detail and location of the defect'			etail and R MAKE		
		7.00 x 0.25 m2	Iocation of the defect' 'C/W POTHOLE 40MI SAFE' 'See attached photog	M PATCH O graphs for o defects'	R MAKE
Item Code	Description of Work		location of the defect' 'C/W POTHOLE 40MI SAFE' 'See attached photog locations of the two	M PATCH O graphs for o defects'	R MAKE details and Quantity
Item Code	·	7.00 x 0.25 m2	location of the defect' 'C/W POTHOLE 40MI SAFE' 'See attached photog locations of the two	M PATCH O graphs for o defects'	R MAKE
tem Code B0160122	Percentage addition 1/13).		location of the defect' 'C/W POTHOLE 40MI SAFE' 'See attached photog locations of the two ory B work. (see Appendix	M PATCH O graphs for o defects'	R MAKE details and Quantity
tem Code B0160122 B0720115	Percentage addition 1/13). Hot poured bitumer width 10mm.	n to rates for Urgency Catego	location of the defect' 'C/W POTHOLE 40MI SAFE' 'See attached photog locations of the two ory B work. (see Appendix riageway, maximum crack	M PATCH O graphs for o defects'	Quantity
Item Code B0160122 B0720115 B1126115	Percentage addition 1/13). Hot poured bitumer width 10mm. Saw cut to bituming	n to rates for Urgency Catego	location of the defect' 'C/W POTHOLE 40MI SAFE' 'See attached photog locations of the two ory B work. (see Appendix riageway, maximum crack th.	M PATCH Or	Quantity 1.00 0.50 0.25
Item Code B0160122 B0720115 B1126115 B2010105	Percentage addition 1/13). Hot poured bitumer width 10mm. Saw cut to bituming COMBINED RATE	n to rates for Urgency Catego n to joints or cracks in the car ous footway, up to 60mm dep	location of the defect' 'C/W POTHOLE 40MI SAFE' 'See attached photog locations of the two bry B work. (see Appendix riageway, maximum crack th. ATCH 60MM THICK	M PATCH Of graphs for or defects' Unit % m m M2	Quantity 1.00 0.50 0.25 0.75
B0160122 B0720115 B1126115 B2010105 B0720115	Percentage addition 1/13). Hot poured bitumer width 10mm. Saw cut to bitumino COMBINED RATE Hot poured bitumer width 10mm.	n to rates for Urgency Catego n to joints or cracks in the car ous footway, up to 60mm dep FOR BITMAC FOOTWAY PA	location of the defect' 'C/W POTHOLE 40MI SAFE' 'See attached photog locations of the two ory B work. (see Appendix riageway, maximum crack th. ATCH 60MM THICK riageway, maximum crack	M PATCH Of graphs for or defects' Unit % m m M2	Quantity 1.00 0.50 0.25 0.75
B0160122 B0720115 B1126115 B2010105 B0720115	Percentage addition 1/13). Hot poured bitumer width 10mm. Saw cut to bitumino COMBINED RATE Hot poured bitumer width 10mm. Saw cut to bitumino	n to rates for Urgency Catego n to joints or cracks in the car ous footway, up to 60mm dep FOR BITMAC FOOTWAY Po n to joints or cracks in the car	location of the defect' 'C/W POTHOLE 40MI SAFE' 'See attached photog locations of the two ory B work. (see Appendix riageway, maximum crack th. ATCH 60MM THICK riageway, maximum crack 40mm depth.	M PATCH Orgraphs for ordefects' Unit % m M2 m	Quantity 1.00 0.50 0.25 0.75
B0160122 B0720115 B1126115 B2010105 B0720115 B0725301 B2010115	Percentage addition 1/13). Hot poured bitumer width 10mm. Saw cut to bituming COMBINED RATE Hot poured bitumer width 10mm. Saw cut to bituming COMBINED RATE	n to rates for Urgency Categor n to joints or cracks in the car ous footway, up to 60mm dep FOR BITMAC FOOTWAY Par n to joints or cracks in the car	location of the defect' 'C/W POTHOLE 40MI SAFE' 'See attached photog locations of the two ory B work. (see Appendix riageway, maximum crack th. ATCH 60MM THICK riageway, maximum crack 40mm depth. AY PATCH 40MM THICK	M PATCH Of graphs for or defects' Unit % m M2 m	Quantity 1.00 0.50 0.25 0.75 0.75 0.23 7.00
B0160122 B0720115 B1126115 B2010105 B0720115 B0725301 B2010115 B0720115	Percentage addition 1/13). Hot poured bitumer width 10mm. Saw cut to bituming COMBINED RATE Hot poured bitumer width 10mm. Saw cut to bituming COMBINED RATE Hot poured bitumer width 10mm.	n to rates for Urgency Categor n to joints or cracks in the car ous footway, up to 60mm dep FOR BITMAC FOOTWAY Pon n to joints or cracks in the car ous bound flexible pavement, FOR BITMAC CARRIAGEW	location of the defect' 'C/W POTHOLE 40MI SAFE' 'See attached photog locations of the two ory B work. (see Appendix riageway, maximum crack th. ATCH 60MM THICK riageway, maximum crack 40mm depth. AY PATCH 40MM THICK riageway, maximum crack	m m m2	Quantity 1.00 0.50 0.25 0.75 0.75
Os 7 & 9 Item Code B0160122 B0720115 B1126115 B2010105 B0720115 B0725301 B2010115 B0725301 B2010115	Percentage addition 1/13). Hot poured bitumer width 10mm. Saw cut to bituming COMBINED RATE Hot poured bitumer width 10mm. Saw cut to bituming COMBINED RATE Hot poured bitumer width 10mm. Saw cut to bituming width 10mm.	n to rates for Urgency Categor to joints or cracks in the car ous footway, up to 60mm dep FOR BITMAC FOOTWAY Par to joints or cracks in the car ous bound flexible pavement, FOR BITMAC CARRIAGEW to joints or cracks in the car	location of the defect' 'C/W POTHOLE 40MI SAFE' 'See attached photog locations of the two ory B work. (see Appendix riageway, maximum crack th. ATCH 60MM THICK riageway, maximum crack 40mm depth. AY PATCH 40MM THICK riageway, maximum crack 40mm depth. AY PATCH 40MM THICK riageway, maximum crack	m m m2 m	Quantity 1.00 0.50 0.25 0.75 0.75 0.23 7.00

Completed on By

		CARRIAGEWAY \	WORKS		
Inspector	Paul Hastings		Order Number	1314054	43
-	URGENCY CATE	EGORY B	FMIS Code	R10005	2N100338
Street Name	HEATHERBROC		Issued Date	23-April	I-2013
Area	BEAUMONT LEYS		Complete by	24-Apr	il-2013
Locations in Stree	 t	Size	Work to do		
jnc Astill Lodo		1.00 x 1.00 m2	'C/W POTHOLE 40MM I SAFE' See attached photogra		
Os No 31		2.00 x 0.75 m2	locations of the two de 'C/W POTHOLE 40MM F SAFE' 'See attached photograp location of the defect'	fects PATCH O	R MAKE
Os No 20		0.75 x 0.75 m2	'C/W POTHOLE 40MM I SAFE' 'See attached photogra location of the defect'		
Os No 9		1.25 x 0.30 m2	'C/W POTHOLE 40MM F SAFE' 'See attached photograp location of the defect'		
Os No 5		6.00 x 0.30 m2 0.75 x 0.50 m2	'C/W POTHOLE 40MM IS SAFE' 'See attached photogration of the defect' 'C/W POTHOLE 40MM IS SAFE' 'See attached photograp location of the defect'	ph for de	etail and R MAKE
	d		'C/W POTHOLE 40MM is SAFE' 'See attached photogration of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photograp	PATCH OF	etail and R MAKE il and R MAKE
Os No 5 jnc Bennion R	d scription of Work	0.75 x 0.50 m2	'C/W POTHOLE 40MM is SAFE' 'See attached photographication of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photographication of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photographication of the defect'	PATCH OF	etail and R MAKE il and R MAKE
Os No 5 jnc Bennion R	scription of Work	0.75 x 0.50 m2 0.50 x 0.50 m2	'C/W POTHOLE 40MM is SAFE' 'See attached photographication of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photographication of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photographication of the defect'	PATCH OF deta PATCH OF deta PATCH OF deta Ph for de	etail and R MAKE il and R MAKE etail and
Os No 5 inc Bennion R tem Code Dec B0160122 Pe 1/1 B0720115 Ho	scription of Work rcentage addition to rate 3).	0.75 x 0.50 m2 0.50 x 0.50 m2 es for Urgency Catego	'C/W POTHOLE 40MM is SAFE' 'See attached photographocation of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photographocation of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photographocation of the defect'	PATCH Of h for deta PATCH O ph for de	etail and R MAKE il and R MAKE etail and
Os No 5 inc Bennion R tem Code Dec 30160122 Pe 1/1 30720115 Ho wic 30725301 Sa	scription of Work rcentage addition to rate 3). t poured bitumen to join lth 10mm. w cut to bituminous bou	0.75 x 0.50 m2 0.50 x 0.50 m2 es for Urgency Catego ts or cracks in the car nd flexible pavement,	'C/W POTHOLE 40MM is SAFE' 'See attached photogral location of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photograp location of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photogral location of the defect' ry B work. (see Appendix riageway, maximum crack 40mm depth.	PATCH Of h for deta PATCH O ph for de Unit % m	etail and R MAKE il and R MAKE etail and Quantity 1.00 1.00
Os No 5 inc Bennion R tem Code Dec 30160122 Pe 1/1 30720115 Ho wic 30725301 Sa	scription of Work rcentage addition to rate 3). t poured bitumen to join lth 10mm. w cut to bituminous bou	0.75 x 0.50 m2 0.50 x 0.50 m2 es for Urgency Catego ts or cracks in the car nd flexible pavement,	'C/W POTHOLE 40MM is SAFE' 'See attached photogral location of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photograp location of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photograp location of the defect' ry B work. (see Appendix riageway, maximum crack	PATCH Of h for deta PATCH O PATCH O Ph for de Unit %	etail and R MAKE il and R MAKE etail and Quantity 1.00 1.00 1.00
Os No 5 inc Bennion R tem Code Dec B0160122 Pe 1/1 B0720115 Ho wic B0725301 Sa B2010115 CC B0720115 Ho	scription of Work rcentage addition to rate 3). t poured bitumen to join th 10mm. w cut to bituminous bou	0.75 x 0.50 m2 0.50 x 0.50 m2 es for Urgency Catego ts or cracks in the car nd flexible pavement, ITMAC CARRIAGEW	'C/W POTHOLE 40MM is SAFE' 'See attached photogral location of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photograp location of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photogral location of the defect' ry B work. (see Appendix riageway, maximum crack 40mm depth.	PATCH Of h for deta PATCH O ph for de Unit % m	etail and R MAKE il and R MAKE etail and Quantity 1.00 1.00
Os No 5 inc Bennion R tem Code Dec B0160122 Pe 1/1 B0720115 Ho wic B0725301 Sa B2010115 CC B0720115 Ho wick	scription of Work recentage addition to rate 3). t poured bitumen to join th 10mm. w cut to bituminous bou MBINED RATE FOR B t poured bitumen to join	0.75 x 0.50 m2 0.50 x 0.50 m2 es for Urgency Categors or cracks in the car and flexible pavement, ITMAC CARRIAGEW ts or cracks in the car	'C/W POTHOLE 40MM is SAFE' 'See attached photogral location of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photograp location of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photogral location of the defect' ry B work. (see Appendix riageway, maximum crack 40mm depth. AY PATCH 40MM THICK riageway, maximum crack	PATCH Of h for deta PATCH Of h for deta PATCH Of h for deta Unit % m m m2	etail and R MAKE il and R MAKE etail and Quantity 1.00 1.00 1.00 2.00
Os No 5 Item Code	scription of Work recentage addition to rate 3). t poured bitumen to join lth 10mm. w cut to bituminous bou MBINED RATE FOR B t poured bitumen to join lth 10mm. w cut to bituminous bou	0.75 x 0.50 m2 0.50 x 0.50 m2 es for Urgency Categors or cracks in the car and flexible pavement, ITMAC CARRIAGEW ts or cracks in the car and flexible pavement, and flexible pavement, and flexible pavement, and flexible pavement,	'C/W POTHOLE 40MM is SAFE' 'See attached photogral location of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photograp location of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photogral location of the defect' ry B work. (see Appendix riageway, maximum crack 40mm depth. AY PATCH 40MM THICK riageway, maximum crack	PATCH Of h for deta PATCH O ph for de Unit % m m m2 m	etail and R MAKE il and R MAKE etail and Quantity 1.00 1.00 1.00 2.00
Os No 5 inc Bennion R Item Code Dec B0160122 Pe 1/1 B0720115 Ho wic B0725301 Sa B2010115 CO B0725301 Sa B0720115 Ho wic B0725301 Sa	scription of Work recentage addition to rate 3). t poured bitumen to join lth 10mm. w cut to bituminous bou MBINED RATE FOR B t poured bitumen to join lth 10mm. w cut to bituminous bou	0.75 x 0.50 m2 0.50 x 0.50 m2 es for Urgency Categors or cracks in the car and flexible pavement, ITMAC CARRIAGEW ts or cracks in the car and flexible pavement, and flexible pavement, and flexible pavement, and flexible pavement,	'C/W POTHOLE 40MM is SAFE' 'See attached photogral location of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photograp location of the defect' 'C/W POTHOLE 40MM is SAFE' 'See attached photogral location of the defect' ry B work. (see Appendix riageway, maximum crack 40mm depth. AY PATCH 40MM THICK riageway, maximum crack 40mm depth.	PATCH Of h for deta PATCH O ph for de Unit % m m m2 m	etail and R MAKE il and R MAKE etail and Quantity 1.00 1.00 1.00 2.00 2.00

B0720115	Hot poured bitumen to joints or cracks in the carriageway, maximum crawidth 10mm.	ack m	0.75
B0725301	Saw cut to bituminous bound flexible pavement, 40mm depth.	m	0.75
B2010115	COMBINED RATE FOR BITMAC CARRIAGEWAY PATCH 40MM THI	CK m2	0.56
B0720115	Hot poured bitumen to joints or cracks in the carriageway, maximum cr width 10mm.	ack m	1.25
B0725301	Saw cut to bituminous bound flexible pavement, 40mm depth.	m	1.25
B2010115	COMBINED RATE FOR BITMAC CARRIAGEWAY PATCH 40MM THI	CK m2	0.38
B0720115	Hot poured bitumen to joints or cracks in the carriageway, maximum cr width 10mm.	ack m	6.00
B0725301	Saw cut to bituminous bound flexible pavement, 40mm depth.	m	6.00
B2010115	COMBINED RATE FOR BITMAC CARRIAGEWAY PATCH 40MM THI	CK m2	1.80
B0720115	Hot poured bitumen to joints or cracks in the carriageway, maximum cr width 10mm.	ack m	0.75
B0725301	Saw cut to bituminous bound flexible pavement, 40mm depth.	m	0.75
B2010115	COMBINED RATE FOR BITMAC CARRIAGEWAY PATCH 40MM THI	CK m2	0.38
B0720115	Hot poured bitumen to joints or cracks in the carriageway, maximum cr width 10mm.	ack m	0.50
B0725301	Saw cut to bituminous bound flexible pavement, 40mm depth.	m	0.50
B2010115	COMBINED RATE FOR BITMAC CARRIAGEWAY PATCH 40MM THI	CK m2	0.25
		Total Cost	£ 187.09

	Leicester	City Council - Highway N	lanagement - Works Order		
		FOOTWAY WO	PRKS		
Inspector	Paul Hastings		Order Number	1314054	6
·	egory URGENCY C	ATEGORY B	FMIS Code	R100055	N100342
Street Name	HEATHERBE	ROOK ROAD	Issued Date	23-April	-2013
Area	BEAUMONT LE		Complete by	24-Apri	I-2013
Locations in	 Street	Size	Work to do		
Os No 39 2.00 x 0.30 m2 'F/W POTHOLE 60MM PATCH OR SAFE WITH BITMAC' See attached photograph for deta location of the defect					
Os No 21 1.00 x 1			'F/W POTHOLE 60MM P SAFE WITH BITMAC' 'See attached photograph locations of the three def	n for deta	
locations of the three defects' Os 14 Bluegates Rd 3.00 x 2.00 m2 'F/W PATCH WITH BINDER COURS 60MM' 'Level out uneven footway caused roots' 'See attached photograph for detail			ed by tree		
Os 2 Blueç	gates Rd	2.00 x 2.00 m2	'C/W POTHOLE 40MM F SAFE' 'Level out uneven footwa roots' 'See attached photograph location of the defect' 'F/W PATCH WITH BINE 60MM'	y caused h for deta	by tree il and
Item Code	Description of Work			Unit	Quantity
B0160122	Percentage addition t	o rates for Urgency Catego	ory B work. (see Appendix	%	1.00
B0720115	Hot poured bitumen to width 10mm.	o joints or cracks in the car	riageway, maximum crack	m	2.00
B1126115	Saw cut to bituminous	s footway, up to 60mm dep	th.	m	2.00
B2010105		OR BITMAC FOOTWAY P		M2	0.60
B0720115	Hot poured bitumen to width 10mm.	o joints or cracks in the car	riageway, maximum crack	m	1.00
B1126115		s footway, up to 60mm dep		m	1.00
B2010105	COMBINED RATE FO	OR BITMAC FOOTWAY P	ATCH 60MM THICK	M2	1.00
B0720115	Hot poured bitumen to width 10mm.	o joints or cracks in the car	riageway, maximum crack	m	3.00
B1126115		s footway, up to 60mm dep		m	3.00
B2010151		R COURSE ONLY PATCH		m2	6.00
B0720115	Hot poured bitumen t width 10mm.	o joints or cracks in the cal	riageway, maximum crack	m 	2.00
B1126115	Saw cut to bituminous	s footway, up to 60mm dep	th.	m	2.00
Completed o	n	Ву			

32010151	FOOTWAY - BINDER COURSE ONLY PATCH 60MM THICK	m2	4.00
		Total Cost	£ 380.99
			<u> </u>
			•

Completed on

LEICESTER CITY COUNCIL - HIGHWAY MANAGEMENT

Page 1 of 1

HIGHWAY INSPECTION REGISTER

Street: MANOR DRIVE, BEAUMONT LEYS WARD

Inspection Schedules: 06/06/2012 - 06/06/2013

From:

.

To:

Inspection Schedule Inspect. Date	Inspect. Date	Inspected By	Works Orders	Notes
000786	10/10/2012	Paul Hastings	12134206	
000824	23/04/2013	Paul Hastings		No repair

Revision 1.4

			CARRIAGEWAY	VORKS			
Inspector	Pá	aul Hastings		Order N	lumber	1213420)6
Urgency Ca	itegory U	RGENCY CATE	GORY B	FMIS C	ode	R10005	2N100338
Street Name	е М	ANOR DRIVE		Issued [Date	10-Octo	ber-2012
Area	ВІ	EAUMONT LEYS V	VARD	Comple	te by	11-Oct	ober-2012
Locations in			Size	Work to do			
Locations in		Road	Size 0.50 x 0.50 m2	'C/W POTHOLE SAFE' See attached ph location of the c	otograp		
	nerbrook	Road ion of Work		'C/W POTHOLE SAFE' See attached ph	otograp		
Jnc Heath	n erbrook Descripti	ion of Work		'C/W POTHOLE SAFE' See attached ph location of the c	otograp lefect	oh for de	tail and
Jnc Heath	Descripti Percent 1/13).	ion of Work age addition to rate	0.50 x 0.50 m2	'C/W POTHOLE SAFE' See attached ph location of the c	notograp lefect endix	oh for de	tail and Quantity
Jnc Heath Item Code B0160122	Descripti Percent 1/13). Hot pou	ion of Work age addition to rate red bitumen to joint Omm.	0.50 x 0.50 m2	'C/W POTHOLE SAFE' See attached ph location of the c y B work. (see Appe	notograp lefect endix	Unit	Quantity 1.00

Completed on	Ву