Inspection Schedules: 01/07/2012 - 31/07/2013

LEICESTER CITY COUNCIL - HIGHWAY MANAGEMENT

HIGHWAY INSPECTION REGISTER

LARCH STREET, CHARNWOOD WARD Street:

From:

.. P

lotes	lo Repairs	
Works Orders		13140056
Inspected By	Andrew Smith	Andrew Smith
Inspect. Date	02/10/2012	03/04/2013
Inspection Schedule Inspect. Date	787000	000822

Revision 1.4

			_		
		FOOTWAY WO	ORKS		
Inspector	Andrew Smith		Order Number	131400	56
Urgency Cat	egory URGENCY CA	TEGORY B	FMIS Code	R10005	5N100342
Street Name	LARCH STRE	ET	Issued Date	03-April-2013	
Area	CHARNWOOD W	/ARD	Complete by	08-Apr	il-2013
Locations in S	Street	Size	Work to do		
o/s Bin are	ea 6	1.00 x m 1.00 x 1.00 m2	'F/W BROKEN KERBS REPLACE WITH NEW OR MAKE SAFE BY REPLACING WITH BITMAC' 1 x 6" x 5" precast kerb required 'F/W UNEVEN/ROCKING KERBS RELAY OR MAKE SAFE BY REPLACING WITH BITMAC' 'F/W AROUND WORKS BITMAC PATCH OR MAKE SAFE' 'F/W UNEVEN/ ROCKING HILOADS 400x400 RELAY OR MAKE SAFE BY REPLACING WITH BITMAC' 'F/W BROKEN HILOADS 400x400 - REPLACE WITH NEW OR MAKE SAFE BY		
o/s 19		x no	REPLACING WITH BITM, '1 x 400 x 400 required' 'F/W MORTAR MISSING/	BROKE	N
			AROUND COVERS, STR ETC. MAKE SAFE BY RE NEW MORTAR'		
tom Codo	Description of Work		•	PLACIN	IG WITH
	Description of Work Percentage addition to recognition to recognition to recognition to recognition to recognition.	rates for Urgency Catego	ETC. MAKE SAFE BY RE NEW MORTAR'		
30160122	Percentage addition to r 1/13).		ETC. MAKE SAFE BY RE NEW MORTAR' ory B work. (see Appendix	Unit	Quantity 1.00
30160122 30210210	Percentage addition to 1/13). Take up or down & disp	ose to contractor's tip. P	erc. MAKE SAFE BY RENEW MORTAR' ory B work. (see Appendix recast kerbing of any size.	Unit %	Quantity 1.00
B0160122 B0210210	Percentage addition to 1/13). Take up or down & disp	ose to contractor's tip. P	ETC. MAKE SAFE BY RE NEW MORTAR' ory B work. (see Appendix	Unit %	Quantity 1.00
B0160122 B0210210 B1105105	Percentage addition to 1/13). Take up or down & disp Precast concrete kerbin 12m radius.	ose to contractor's tip. P	erc. MAKE SAFE BY RENEW MORTAR' ory B work. (see Appendix recast kerbing of any size.	Unit %	Quantity 1.00
30160122 30210210 31105105 32010107	Percentage addition to 1/13). Take up or down & disp Precast concrete kerbin 12m radius. COMBINED RATE FOR KERBS	ose to contractor's tip. P ng 125 * 250mm. Laid str R LIFTING AND RELAYI	erc. MAKE SAFE BY RENEW MORTAR' ory B work. (see Appendix recast kerbing of any size. raight or curved exceeding	Unit %	Quantity 1.00 1.00
B0160122 B0210210 B1105105 B2010107 B0720115	Percentage addition to 1/13). Take up or down & disperimental precast concrete kerbing 12m radius. COMBINED RATE FOR KERBS Hot poured bitumen to juict 10mm. Saw cut to bituminous for the second precast concrete kerbing 12m radius.	ose to contractor's tip. P g 125 * 250mm. Laid str R LIFTING AND RELAYI oints or cracks in the car ootway, up to 60mm dep	erriageway, maximum crack	Unit % m m m m	Quantity 1.00 1.00 1.00 0.00 3.00
30160122 30210210 31105105 32010107 30720115	Percentage addition to r 1/13). Take up or down & disp Precast concrete kerbin 12m radius. COMBINED RATE FOR KERBS Hot poured bitumen to judth 10mm. Saw cut to bituminous for COMBINED RATE FOR	ose to contractor's tip. Pag 125 * 250mm. Laid str R LIFTING AND RELAYI oints or cracks in the car ootway, up to 60mm dep R BITMAC FOOTWAY P	ETC. MAKE SAFE BY RENEW MORTAR' ory B work. (see Appendix recast kerbing of any size. raight or curved exceeding NG PRE-CAST CONCRETE riageway, maximum crack oth. ATCH 60MM THICK	Unit % m m m M2	Quantity 1.00 1.00 1.00 0.00 3.00 3.00 1.50
B0160122 B0210210 B1105105 B2010107 B0720115 B1126115 B2010105	Percentage addition to r 1/13). Take up or down & disp Precast concrete kerbin 12m radius. COMBINED RATE FOR KERBS Hot poured bitumen to judth 10mm. Saw cut to bituminous for COMBINED RATE FOR	ose to contractor's tip. Pag 125 * 250mm. Laid str R LIFTING AND RELAYI oints or cracks in the car ootway, up to 60mm dep R BITMAC FOOTWAY P	erriageway, maximum crack	Unit % m m m m	Quantity 1.00 1.00 1.00 0.00 3.00
B0160122 B0210210 B1105105 B2010107 B0720115 B1126115 B2010105 B2010103	Percentage addition to 1/13). Take up or down & disperimental disperiments of the policy of the pol	ose to contractor's tip. Pose to contractor's tip. Pose to 250mm. Laid structured and RELAYI oints or cracks in the care cotway, up to 60mm department of RELAYI POST AND RELATIONS OF TAKING UP AND TAKING	ETC. MAKE SAFE BY RENEW MORTAR' ory B work. (see Appendix recast kerbing of any size. raight or curved exceeding NG PRE-CAST CONCRETE riageway, maximum crack oth. ATCH 60MM THICK	Unit % m m m M2	Quantity 1.00 1.00 1.00 0.00 3.00 3.00 1.50
B0160122 B0210210 B1105105 B2010107	Percentage addition to 1/13). Take up or down & disp Precast concrete kerbin 12m radius. COMBINED RATE FOR KERBS Hot poured bitumen to j width 10mm. Saw cut to bituminous for COMBINED RATE FOR COMBINED RATE FOR OR 450X450 Take up or down & disp size. Precast concrete slabs,	ose to contractor's tip. P ig 125 * 250mm. Laid str R LIFTING AND RELAYI oints or cracks in the car ootway, up to 60mm dep R BITMAC FOOTWAY P R TAKING UP AND RELA ose to contractor's tip. P	erc. MAKE SAFE BY RENEW MORTAR' ory B work. (see Appendix Precast kerbing of any size. Precast or curved exceeding PRE-CAST CONCRETE Priageway, maximum crack oth. ATCH 60MM THICK AYING HI-LOADS 400X400	Unit % m m m M2 M2	Quantity 1.00 1.00 1.00 0.00 3.00 3.00 1.50 1.00
B0160122 B0210210 B1105105 B2010107 B0720115 B1126115 B2010105 B2010103 B0210205	Percentage addition to 1/13). Take up or down & disp Precast concrete kerbin 12m radius. COMBINED RATE FOR KERBS Hot poured bitumen to j width 10mm. Saw cut to bituminous for COMBINED RATE FOR OR 450X450 Take up or down & disp size. Precast concrete slabs, on sand bed 25mm thic	ose to contractor's tip. Pag 125 * 250mm. Laid stress LIFTING AND RELAYI oints or cracks in the care cotway, up to 60mm departments of the contractor's tip. Page 155mm thick, in footway k, surface sloping at 10 cross to contractor's tip.	erc. MAKE SAFE BY RENEW MORTAR' ory B work. (see Appendix recast kerbing of any size. raight or curved exceeding NG PRE-CAST CONCRETE raigeway, maximum crack oth. ATCH 60MM THICK AYING HI-LOADS 400X400 raving slabs of any material or or paved areas, 400 * 400mm	Unit % m m m M2 M2 m2	Quantity 1.00 1.00 1.00 0.00 3.00 3.00 1.50 1.00 0.16

			Total Cost	£ 165.53
	 	 .		
Completed on	Ву			